

LINEAR TRAY SEALER

Thirty years of MAP sealing, three trays every cycle.

3 TRAYS PER CYCLE

UP TO **43** TRAYS A MINUTE

24 IN. FILM WIDTH

MAP with gas mixer. 304 stainless steel. Touch screen control.



HERA-X

Ideal Solution for:

Meat and fish, fresh produce, ready meals, frozen food, baked goods, dairy, pasta and nuts.

Tailored completely to your unique packaging specifications and production workflow.



Meat



Poultry



Vegetables



Ready Meals



Baked Goods

Specifications

STANDARD		TECHNICAL DATA	
Body	304 stainless steel	Capacity	40 to 43 trays / min
Control	Touch screen, three heat zones	Cycle speed	13 to 14 cycles / min
Trays per cycle	3	Film width	24.4 in / 620 mm
Modified atmosphere	Gas mixer sets the ratio	Film roll	Up to 10.2 in / 260 mm diameter
Sealing film	Roll stock, 25 to 80 micron	Dimensions	101.8 x 38.2 x 58.3 in / 2,585 x 970 x 1,480 mm
Max tray size	6.3 x 11.0 x 2.4 in / 160 x 280 x 60 mm	Net weight	1,323 lb / 600 kg
Pneumatics	Integrated, French components	Electrical	380V / 50 Hz, 2.4 kW, 3 phase + neutral + ground
		Working air	87 to 116 psi / 0.6 to 0.8 MPa

Gas purity of 99.9 percent or better is recommended, and the mix is verified with a gas analyser. Rates are nominal; utilities, footprint and weight are confirmed at quotation.



**Tell us your product
and tray format.**

We will come back with the full specification for your line.

Hefestus USA Inc.

6280 South Valley View Boulevard, Suite 608
Las Vegas, NV 89118
702-881-1970
office@hefestus-tech.com